

CLAIMS

What is claimed is:

1. A reproduction-only optical information storage medium comprising:
a plurality of areas; and
at least one transition area, wherein each transition area is located between two adjacent areas.
2. The optical information storage medium of claim 1, wherein data is recorded in the form of pits in the areas and the transition area.
3. The optical information storage medium of claim 2, wherein a pit pattern of the transition area is the same as a pit pattern of an area preceding the transition area.
4. The optical information storage medium of claim 2, wherein a pit pattern of the transition area is the same as a pit pattern of an area following the transition area.
5. The optical information storage medium of claim 1, wherein the transition area is a mirror area.
6. The optical information storage medium of claim 2, wherein pits of the transition area are formed in one of a straight pattern and a wobbling pattern.
7. The optical information storage medium of claim 6, wherein the straight pattern is one of a straight single pattern, a straight specific pattern, and a straight random pattern.
8. The optical information storage medium of claim 6, wherein the wobbling pattern is one of a wobbling single pattern, a wobbling specific pattern, and a wobbling random pattern.
9. The optical information storage medium of claim 2, wherein a track pitch of pits in the transition area is the same as track pitches of pits in the adjacent areas.
10. The optical information storage medium of claim 4, wherein the track pitch of pits in the transition area and the track pitches of pits in the adjacent areas differ.

11. The optical information storage medium of claim 4, wherein the track pitch of pits in the transition area are the same as the track pitch of pits in one of the adjacent areas.

12. The optical information storage medium of claim 10, wherein the track pitch of pits formed in the transition area gradually one of increases and decreases from the track pitch of pits formed in of the area preceding the transition area to the track pitch of pits formed in the area following the transition area.

13. The optical information storage medium of claim 6, wherein when pits for the transition area is formed in a wobbling pattern, the amplitude of a wobble gradually decreases or increases.

14. The optical information storage medium of claim 1, wherein the transition area stores information identifying a transition area.

15. A reproduction-only optical information storage medium comprising:
a burst cutting area (BCA);
a lead-in area;
a user data area;
a lead-out area; and
a transition area located in at least one of an area between the BCA and the lead-in area, an area between the lead-in area and the user data area, and an area between the user data area and the lead-out area,
wherein the BCA, the lead-in area, the user data area, and the lead out area are formed of pits.

16. The optical information storage medium of claim 15, wherein a first transition area is included between the BCA and the lead-in area, and the BCA, the lead-in area, and the first transition area are each formed of pits in one of a straight pattern and a wobbling pattern.

17. The optical information storage medium of claim 15, wherein a second transition area is included between the lead-in area and the user data area, and the lead-in area, the user

data area, and the second transition area are each formed of pits on one of a straight pattern and a wobbling pattern.

18. The optical information storage medium of claim 17, wherein the straight pattern is one of a straight single pattern, a straight specific pattern, and a straight random pattern.

19. The optical information storage medium of claim 17, wherein the wobbling pattern is one of a wobbling single pattern, a wobbling specific pattern, and a wobbling random pattern.

20. The optical information storage medium of claim 16, wherein a track pitch of pits formed in the BCA, a track pitch of pits formed in the first transition area, a track pitch of pits formed in the lead-in area are the same.

21. The optical information storage medium of claim 16, wherein a track pitch of pits formed in the BCA, a track pitch of pits formed in the first transition area, a track pitch of pits formed in the lead-in area are different from one another.

22. The optical information storage medium of claim 21, wherein the track pitch of pits formed in the first transition area gradually one of increases and decreases from the track pitch of pits formed in the BCA to the track pitch of pits formed in the lead-in area.

23. The optical information storage medium of claim 17, wherein a track pitch of pits formed in the lead-in area, a track pitch of pits formed in the second transition area, a track pitch of pits formed in the user data area are the same.

24. The optical information storage medium of claim 17, wherein a track pitch of pits formed in the lead-in area, a track pitch of pits formed in the second transition area, a track pitch of pits formed in the user data area are different.

25. The optical information storage medium of claim 24, wherein the track pitch of pits formed in the second transition area gradually increases or decreases from the track pitch of pits formed in the lead-in area to the track pitch of pits formed in the user data area.

26. The optical information storage medium of claim 16, wherein when pits for the first transition area are formed in a wobbling pattern, the amplitude of a wobble gradually one of decreases and increases.

27. The optical information storage medium of claim 17, wherein when pits for the second transition area are formed in a wobbling pattern, the amplitude of a wobble gradually decreases or increases.

28. The optical information storage medium of claim 17, wherein each of the first and second transition areas stores information identifying the corresponding transition area.

29. A reproduction-only optical information storage medium comprises:
a burst cutting area (BCA);
a lead-in area;
a user data area;
a lead-in area; and
a transition area,
wherein at least one of the BCA, the lead-in area, the user data area, and the lead-out area is divided into a plurality of sub-areas, and
wherein the transition area is located between two adjacent sub-areas.

30. The optical information storage medium of claim 29, wherein pits for the sub-areas and pits for transition area are each formed in a straight pattern or a wobbling pattern.

31. The optical information storage medium of claim 30, wherein the straight pattern is one of a straight single pattern, a straight specific pattern, and a straight random pattern.

32. The optical information storage medium of claim 30, wherein the wobbling pattern is one of a wobbling single pattern, a wobbling specific pattern, and a wobbling random pattern.